WHAT IS CLAIMED IS:

1. A multiple priority non-blocking load buffer comprising:

    a plurality of variable depth pending queues for queuing entries of memory or I/O requests generated by processors to peripheral devices, each of said pending queues including a plurality of sub-queues; and

    a variable length return queuing unit for buffering data returned from said peripheral devices in response to said I/O requests.

2. A multiple priority non-blocking load buffer according to Claim 1, wherein said variable length return queuing unit comprises one variable length return queue.

3. A multiple priority non-blocking load buffer according to Claim 1, wherein said variable length return queuing unit comprises a plurality of variable length return queues.

4. A multiple priority non-blocking load buffer according to Claim 3, wherein each of said plurality of variable length return queues corresponds to each of said processors.

5. A multiple priority non-blocking load buffer according to Claim 3, wherein each of said plurality of variable length return queues corresponds to each of said peripheral devices.

6. A multiple priority non-blocking load buffer according to Claim 3, wherein each of said plurality of variable length return queues corresponds to a unique priority level.

7. A multiple priority non-blocking load buffer according to Claim 1, wherein each of said sub-queues within one of said pending queues is assigned a unique priority level.

8. A multiple priority non-blocking load buffer according to Claim 7,
5   wherein said I/O requests include an address and a priority tag, said address directs said memory or I/O requests to a corresponding one of said pending queues and said priority tag channels said memory or I/O requests to a corresponding one of said sub-queues within the one said pending queue.

9. A multiple priority non-blocking load buffer according to Claim 8,
10 wherein each of said pending queues comprises a priority controller for issuing said memory or I/O requests from said sub-queues in a highest priority first manner.

10. A multiple priority non-blocking load buffer comprising:

a variable depth pending queue for queuing entries of I/O requests generated by a processor to peripheral devices, said pending queue including a
15 plurality of sub-queues; and

a variable length return queuing unit for buffering data returned from said peripheral devices in response to said memory or I/O requests.

11. A multiple priority non-blocking load buffer according to Claim 10, wherein said variable length return queuing unit comprises one variable length
20 return queue.

12. A multiple priority non-blocking load buffer according to Claim 10, wherein said variable length return queuing unit comprises a plurality of variable length return queues.

13.   A multiple priority non-blocking load buffer according to Claim 12, wherein each of said plurality of variable length return queues corresponds to each of said peripheral devices.

14.   A multiple priority non-blocking load buffer according to Claim 12, wherein each of said plurality of variable length return queues corresponds to a unique priority level.

15.   A multiple priority non-blocking load buffer according to Claim 10, wherein each of said sub-queues within said pending queues is assigned a unique priority level.

16.   A multiple priority non-blocking load buffer according to Claim 15, wherein said memory or I/O requests include a priority tag, said priority tag channels said memory or I/O requests to a corresponding one of said sub-queues.

17.   A multiple priority non-blocking load buffer according to Claim 16, wherein said pending queue comprises a priority controller for issuing said memory or I/O requests from said sub-queues in a highest priority first manner.

(once Amended)

18.   A method for limiting admission of prioritized memory or I/O transactions for storage in a memory comprising:

(a) dividing the memory into a plurality of queues having unique priority levels;

(b) channeling said prioritized memory or I/O transactions to the ones of said queues having its unique priority level corresponding to said prioritized memory or I/O transactions;

(c) storing said prioritized memory or I/O transactions in the corresponding queues when space is available therein; and

(d) storing said prioritized memory or I/O transactions in one of said queues having a priority level which is one priority level less than the unique priority level corresponding to said prioritized memory or I/O transactions channeled at said step (b) when the space available in the queues corresponding to said prioritized memory or I/O transactions is exceeded.

19. A method according to Claim 18, wherein the memory is contained within a non-blocking load buffer.

20. A method according to Claim 18, wherein said memory or I/O transactions comprise loads and stores.